## **EVOLUTION® 6000 Basic Thermal Imaging Camera**



## Provides easy-to-use TIC performance – a simplified fireground tool.

- Economical, durable value to fit your budget
- NFPA 1801-compliant
- Save on repair costs with rugged, waterproof and shock-resistant product design
- 320X240 high definition image quality offers excellent resolution
- Standard flashlight provides extra visibility for firefighter proximity to enhance safety and situational awareness
- Laser pointer pinpoints hot spots and other areas of interest to allow others to take fast, specific action
- Patented dual-handle design for easy handoff on the fireground
- Three carabiner attachment points offer flexibility in attaching camera to firefighter





Colorized basic image



Three carabiner attachment points



Patented dual-handle design



Field-replaceable germanium lens





Flashlight/laser pointer



## **Technical Specifications**

CONSTRUCTION	Flame retardant (material passes NFPA direct flame exposure test). IP67 [withstands immersion to 3 ft (1 meter)]
APPROXIMATE DIMENSIONS	7.3" x 4.8" x 11.6" (LxWxH) (185 mm x 122 mm x 295 mm)
SENSOR	Uncooled VOX microbolometer
ARRAY SIZE	320X240
WEIGHT	2.65 lbs (1.2 kg)
POWER SOURCE	Rechargeable lithium-ion battery

OPERATING TIME	3.5 hours at nominal 72°F (22°C)
FIELD OF VIEW	48° H; 37° V
INTRINSICALLY SAFE	Nonincendive equipment (UL Class 1, Div 2)
APPROVALS	NFPA 1801, 2013 Edition-compliant
NET EQUIVALENT TEMPERATURE DIFFERENCE	High Sensitivity 40 mK (0.040°C) (typical), 78 mK (0.078°C) (max) Low Sensitivity 234 mK (0.234°C)
ENVIRONMENTAL AMBIENT TEMPERATURE AND OPERATING TIME	176° F (80°C) > 30 minutes 248° F (120°C) > 20 minutes 500° F (260°C) > 6 minutes -22° F (-30°C) > 40 minutes -40° F (-40°C) > 25 minutes

## **Ordering Information**

EVOLUTION B	DLUTION BASIC 6000 TIC	
10145938	EVOLUTION 6000 Basic TIC (includes flashlight, laser pointer, degrees F)	
10145939	EVOLUTION 6000 Basic TIC (includes flashlight, laser pointer, degrees C)	

EVOLUTION 6000 CHARGING KITS	
10145750	EVOLUTION 6000 TIC Station Kit (includes carrying case, 2 rechargeable batteries, multi-use charger (North America), retractable lanyard, and carabiner)
10145771	EVOLUTION 6000 TIC Vehicle Kit (includes 2 rechargeable batteries, vehicle charger, retractable lanyard, and carabiner)

ACCESSORIES	
10145859	Multi-use charger (12V) kit
10148136	Vehicle mounted charger system
10147390	Vehicle mounting bracket
10145749	Reflective label ID kit (includes 3 sets of reflective ID labels)
10120606-SP	Lithium-ion battery
10145748	Tripod adapter
10040005	Carabiner
10127441-SP	Plastic carrying case
10040226	Retractable lanyard
10039515	Shoulder strap
10039516	Wrist strap
10148391-SP	Protective display covers (3 per package)

Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

ID 3460-16-MC / Mar 2013 © MSA 2013 Printed in U.S.A.

MSA Corporate Center 1000 Cranberry Woods Drive Cranberry Township, PA 16066 USA Phone 724-776-8600 www.MSAsafety.com

**U.S. Customer Service Center** 

1-800-MSA-2222 Phone Fax 1-800-967-0398 MSA Canada

1-800-672-2222 Phone 1-800-967-0398 Fax

MSA Mexico

01 800 672 7222 Fax 52 - 44 2227 3943

MSA International

724-776-8626 Phone Toll Free 1-800-672-7777 724-741-1559 Email msa.international@MSAsafety.com

Offices and representatives worldwide