

MEDIUM-PRESSURE LIFTING BAGS 1.0 bar (14.5 psi) **1.5.**



Perfect performance on soft grounds

Suitable for high lifts

ADAPTERS

Made from extra durable materials

Extra fast inflation and deflation

CONTROLLERS



SINGLE FITTING CONTROLLER 1.0 bar (14.5 psi) 1.0 kg (2.2 lbs) 551503



SHUT-OFF + SAFETY VALVE 1.0 bar (14.5 psi) 0.4 kg (0.88 lbs) 551504



DOUBLE FITTING CONTROLLER 1.0 bar (14.5 psi) 2.0 kg (4.4 lbs) 504061



ADAPTER GEKA/26 0.1 kg (0.2 lbs)
575711



ACCESSORIES

DOUBLE DEADMAN CONTROLLER PLASTIC BOX 1.0 bar (14.5 psi) 3.0 kg (6.6 lbs) 528119

CARRY-ON VALISE

(for two bags)



REPAIR KIT 0.09 kg (0.2 lbs)
522050



1.0 kg (2.2 lbs) 521483 MA 1.3 kg (2.9 lbs) 521485 MB 1.5 kg (3.3 lbs) 521486 MC 2.0 kg (4.4 lbs) 521487 MD

INFLATION HOSES



TYPE 5 m (16') **10 m** (33')

 RED
 2.2 kg (4.9 lbs) 525662
 3.0 kg (6.6 lbs) 538935

 YELLOW
 2.7 kg (6 lbs) 504063
 5.0 kg (11 lbs) 519817

 BLACK
 1.7 kg (3.7 lbs) 504064
 1.4 kg (3 lbs) 577464

TECHNICAL DATA

TECHNICAL DATA										
ТҮРЕ	PART NUMBER	DIMENSIONS		WEIGHT	WORKING	NOMINAL	AIR	MAX LIFTING	MAX. LIFTING	INFLATION
		DIAMETER	HEIGHT	WEIGHT	PRESSURE	CONTENT	REQUIREMENT	CAPACITY	HEIGHT	VALVE
		[cm] / [inch]	[cm] / [inch]	[kg] / [lbs]	[bar] / [psi]	[I] / [cu./Ft.]	[I] / [cu./Ft.]	[t] / [US Tons]	[cm] / [inch]	Thread size
MA	521478	61 / 24"	5 / 2"	7.5 / 17	1.0 / 14.5	126 / 4	251 / 9	3 / 3 . 3	43 / 17"	R 3/8" - male
MB	521479	76 / 30"	5 / 2"	12 / 27	1.0 / 14.5	268 / 9	535 / 19	4.7 / 5 . 2	59 / 23"	R 3/8" - male
MC	521481	91 / 36"	5 / 2"	15 / 33	1.0 / 14.5	397 / 14	793 / 28	6.7 / 7.4	61 / 24"	R 3/8" - male
MD	521482	122 / 48"	8 / 3"	35 / 77	1.0 / 14.5	1168 / 41	2337 / 83	12 / 13 . 2	100 / 39"	R 3/8" - male

