



Type CLAW

## LOW-PRESSURE LIFTING BAGS 0.5 bar (7.3 psi)

1. 2.

Low-pressure lifting bags are used for lifting very large objects. They have special TOP GRIP pads bonded to the top and bottom of the bag. Top Grip pad offers heavy duty protection from slipping, puncture, abrasion and premature wear. Used for uprighting trucks, rail cars, and other types of vehicles or structures.

0.5  
BAR

Lifting height  
up to 2.1 m

Ideal for towing  
recovery

Special  
TOP GRIP pads

Use on all grounds  
(rock, glass, metal)

### CONTROLLERS



**SINGLE FITTING  
CONTROLLER**  
0.5 bar (7.3 psi)  
1.0 kg (2.2 lbs)  
553361




**DOUBLE FITTING  
CONTROLLER**  
0.5 bar (7.3 psi)  
2.5 kg (5.5 lbs)  
507801




**FKT CONTROLLER**  
40.0 kg (88 lbs)  
4-port - 545631  
53.0 kg (117 lbs)  
6-port - 545632  
\*Other sizes on  
request

### ADAPTERS



**SHUT-OFF  
+ SAFETY VALVE**  
0.5 bar (7.3 psi)  
0.4 kg (0.8 lbs)  
577465




**ADAPTER CLAW/26**  
0.15 kg (0.33 lbs)  
529704



**VACUUM/BLOWER**  
124.0 kg (273 lbs)  
598159

### ACCESSORIES






**PROTECTION PLATE  
WOOD+TOP GRIP**  
11.0 kg (24 lbs)  
581227



**REPAIR KIT**  
0.1 kg (0.22 lbs)  
522050

### INFLATION HOSES



TYPE	5 m (16')	15 m (49')
	2 kg (4.4 lbs)	5 kg (11 lbs)
<b>RED RIGID</b>	595741	594222
<b>GREY RIGID</b>	595744	594220
<b>YELLOW RIGID</b>	595743	594221
<b>GREEN RIGID</b>	586722	586724



### TECHNICAL DATA

TYPE	PART NUMBER	DIMENSIONS		WEIGHT	WORKING PRESSURE	NOMINAL CONTENT	AIR REQUIREMENT	MAX LIFTING CAPACITY	MAX. LIFTING HEIGHT	INFLATION VALVE
		DIAMETER	HEIGHT							
		[cm] / [inch]	[cm] / [inch]							
MS 45	527296	102 / 40"	10 / 4"	16 / 35	0.5 / 7.3	368 / 13	551 / 20	4 / 4.4	45 / 18"	R 1/2"-female
MS 122	527297	135 / 53"	10 / 4"	30 / 66	0.5 / 7.3	1745 / 62	2618 / 93	7 / 7.7	122 / 48"	R 3/4"-male
MS 210	527298	145 / 57"	10 / 4"	43 / 95	0.5 / 7.3	3466 / 122	5199 / 184	9 / 9.9	210 / 83"	R 3/4"-male